

Manhattan Gas Fire Table - Technical Specification

Dimensions	500mm (H) x 1000mm (W) x 1000mm (L)		
Weight (Kg) ¹	110 Installed	170 Shipping	
Footprint	735mm x 735mm		
Installation	Product comes fully packaged in its own crate and requires at least 2x People for safe installation		
Burner type	Rivelin PF50 CE approved Gas Burner		
Manual available in	English, French, German, Spanish		
Fuel Type - Natural Gas (NG)	G20 (I2H, I2E, I2E+)	G25 (I2E+, I2ELL, I2L)	
NG Countries of Destination	AT, BE, BG, CH, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, IE, IT, LT, LU, LV, NO, PL, PT, RO, SE, SI, SK, TR	BE, DE, FR, NL	
Fuel Type LPG	Propane I3P - 37mbar	Propane I3P - 50**mbar	
LPG Countries of Destination	BE, CH, CZ, ES, FR, GB, GR, HR, IE, IT, LT, NL, PL, PT, SI, SK	AT, CH, CZ, DE, GR, NL, SK	
UK & IE Fuel Type*	Natural Gas (G20)	LPG Propane (G31) 19kg or larger	
Ignition type	Manual or remote	Manual or remote	
Heat Output	18kw	18kw	
Max Flow rates*	1.7 (m ³ /hr)	0.66 (m ³ /hr)	
Supply pressure*	20 (mbar)	37 (mbar)	
Connection type	1/2 " BSP male or female fitting located on the end of a 400mm stainless steel flexible hose	8mm compression fitting located on the end of a 400mm stainless steel flexible hose	
Gas Valve height	325mm		
Fuel supply	Must be piped to underside of table		
Electricity supply	ONLY required for LEDs and to upgrade Remote Control Ignition to 240V - Must be channelled to underside of table		
Ventilation	<p>The fire table incorporates the versatile Rivelin PF50 burner. The table shall only be used in an above ground situation, without stagnant areas, where gas leakage and products of combustion are rapidly dispersed by wind and natural convection.</p> <p>The following are recommendations only and may or may not comply with your local council standards. Please check with your local council for actual building standards. Typically an outdoor space is not enclosed but, any enclosure in which the appliance is used should comply with one of the following:</p> <ul style="list-style-type: none"> • An enclosure with walls on all sides, but at least one permanent opening at ground level and no overhead cover. • Within a partial enclosure that includes an overhead cover and no more than two walls • Within a partial enclosure that includes an overhead cover and more than two walls, the following should apply: <ul style="list-style-type: none"> • At least 25% of the total wall area is completely open, and • At least 30% of the remaining wall area is open and unrestricted <p>*Consult Manual for latest up to date information</p>		
Distance to combustibles	Above Table - 2.5 m Below Table - 250mm Sides (all round) - 750mm		
LEDs	Warm	Extra Warm	RGB
Kelvin Rating	3000-3500k	2700 - 3000	
Power source	240v	240v	240v
Control	App or Remote	App or Remote	App or Remote

Please note: This model is classed as a permanent gas connection and therefore it's the buyer's responsibility to obtain confirmation from their gas safe registered installer that the site has approval for the safe installation and operation of a Rivelin gas appliance.

¹ Weights can vary depending on specification

*The specification is for the UK and Ireland. For specific technical specifications for non UK installations where gas flows and pressures vary please contact us. Whilst we always look to maintain and keep the information contained on the website completely up to date, from time to time information can change. Please always consult us for the most up to date information

** NOTE - for appliances using Propane at 50mbar, a regulator will be supplied with the appliance to reduce the pressure to 37mbar.